

Area of Application

ESSVE Roofing screw DECOR with reduced drillpoint designed for the installation of profiled sheet-metal against wood and sheet-metal-against-sheet-metal (overlap).

Description

The screw is produced in hardened carbon steel with bright zinc plated surface treatment and polyester powder coated. The screw has an EPDM seal that provides weatherproof installation. It has a low pan head with a diameter of 14.0 mm and is designed so the EPDM rubber is concealed when fitted. This

head shape gives an aesthetic installation where you do not want a visible hex head. The screw is fitted with TX-bit drive.

Installation

The screw must not be overtightened during installation, as this can damage the EPDM seal and the requirement of weatherproof installation may be compromised. Recommended rpm: 1 100-2500/min.



Specification

Material	Hardened steel SAE 1022
Surface treatment	Bright zinc plated and painted. 40-50 µm polyester powder coating
Washer	Black EPDM seal
Usage	Approx. 8 per metre ²
Corrosion category	C3

Roofing screw DECOR

ESSBOX

Item no.	Dimension dk x L mm	D mm	Drill capacity mm	Colour	Colour code	Bit no	ESSBOX size	Qty/pack.
63260	4.8 x 20	14.0	4 x 0.7	Silver	RAL9006	TX25	204	250
63262	4.8 x 20	14.0	4 x 0.7	Black	RAL9011	TX25	204	250
63258	4.8 x 20	14.0	4 x 0.7	Red	RAL3009	TX25	204	250
63256	4.8 x 20	14.0	4 x 0.7	White	RAL9010	TX25	204	250
63254	4.8 x 20	14.0	4 x 0.7	Light grey	RAL7035	TX25	204	250
63269	4.8 x 20	14.0	4 x 0.7	Graphite grey	RAL7024	TX25	204	250
63252	4.8 x 20	14.0	4 x 0.7	Brick red	RAL8004	TX25	204	250
63284	4.8 x 35	14.0	4 x 0.7	Silver	RAL9006	TX25	304	250
63274	4.8 x 35	14.0	4 x 0.7	Black	RAL9011	TX25	304	250
63276	4.8 x 35	14.0	4 x 0.7	Red	RAL3009	TX25	304	250
63278	4.8 x 35	14.0	4 x 0.7	White	RAL9010	TX25	304	250
63280	4.8 x 35	14.0	4 x 0.7	Light grey	RAL7035	TX25	304	250
63281	4.8 x 35	14.0	4 x 0.7	Graphite grey	RAL7024	TX25	304	250
63282	4.8 x 35	14.0	4 x 0.7	Brick red	RAL8004	TX25	304	250

