

Area of Application

ESSVE Flooring screw is designed for installation in solid wooden floors, floor and base boards, etc. indoors, against wood. For installation of harder wooden floors e.g. oak so pre-drilling is necessary.

Description

The screw is produced in hardened carbon steel with yellow chromate surface treatment. It is equipped with a square drive no. R1. Each

250 pack includes 1 x bit no. R1.

The screw is equipped with a reduced drill-point to avoid cracking.

Installation

For installation the screw should be driven in at a 45 degree angle on the floor board's spring side and with approx. 600 mm screw spacing.

Recommended rpm: 400-1200/min.



Specification


Material	Hardened steel SAE C1018
Surface treatment	Yellow chromate 5 µm
Corrosion category	C1

Screw recommendation

Floor thickness mm	Screw dimension mm
14.0	3,9×42
21.0	3,9×58
25.0	3,9×58
30.0	3,9×58

Flooring screw for solid wood flooring, yellow chromate

ESSBOX



©FELLA-VELO

Item no.	Dimension dk x L mm	D mm	B mm	Bit no	ESSBOX size	Qty/pack.	Pack./large pack.
567142	3,9 × 42	5,6	25,0	R1 Square	203	250	8
567158	3,9 × 58	5,6	35,0	R1 Square	204	250	6
1 x Square bit no.1 supplied in each 250-pack.							