

Area of Application

ESSVE Duck Foot is a new patented drywall fixing that easily and quickly provides a strong and secure mounting in both single and double drywall. Ideal areas of application are Modular shelf rails, brackets, wall units, TV mounts, lamps, etc.

Description

Duck Foot works in both single and double drywall. The integrated drill ensures that the hole is the right dimensions. The supplied screw is 5 mm and permits an object thickness up to max. 22 mm. Installation is carried out using a screwdriver and a PH2 standard bits.



Installation

- 1. Connect Duck Foot's bits shaped head to your bit holder. Drill the anchor directly into the wall. Drilling is finished when the plastic leg touches the wall.**
- 2. Bend down the plastic leg and push Duck Foot into the drilled hole.**
- 3. Press the screw through the object to be fixed and then into the plastic leg Duck Foot.**
- 4. Tighten the screw until it stops. What happens behind the wall is that the screw collects the anchor part while the plastic tube expands into the drilled hole. Installation is finished!**

Specification

	Duck Foot	Screws
Material	Zinc and PE plastic	Zinc plated steel

Drywall anchor Duck Foot

ESSBOX

Item no.	Designation	Screws	Maximum detail thickness mm	ESSBOX size	Qty/ pack.	Pack./ large pack.	Item code
191140	Drywall anchor Duck Foot	M5	25	204	35	6	L
511286	Drywall anchor Duck Foot (small package)	M5	25		4	10	L

Designation	Drywall size mm	Tension load (N) (kg)	Shear load (V) kg
Duck Foot	13	25	40
Duck Foot	2×13	40	50