



# ENVIRONMENTAL PRODUCT DECLARATION

*In accordance with ISO 14025 and ISO 21930*

## Gyproc® Golvgips – Floor Board

Verification Date : 2 July 2013

Version : 1.0



The environmental impacts of this product have been assessed over its whole life cycle. Its Environmental Product Declaration has been verified by an independent third party.

REGISTRATION N°

EPD No: S-P-00392



# Gyproc

SAINT-GOBAIN

# Environmental Product Declaration

|| ISO 14025 & ISO 21930 || Approved according to ISO 14025: §8.1.4 || EPD® PCR: 01 Construction Products ||

|| EPD Type: Cradle to grave || Year of study: 2012 - Valid until: 2018-06-30 ||



## Gyproc® Golvgips – Floor Board

|| EPD №: S-P-00392 || Market area: Sweden, Norway ||

Gyproc Golvgips is a plasterboard used as foundation for flooring where an appropriate combination of high weight, high rigidity and low thickness is required. The high density provides improved airborne and impact sound insulation, the enhanced surface hardness provides impact resistance and the enhanced board strength provides increased longitudinal and transverse breaking loads. It also provides good fire protection and it is an excellent base for ceramic tiles. It is 12.5 mm thick, available in 600 mm width (GG 13).

### Product information:

Functional unit (FU): m<sup>2</sup> installed plasterboard with expected service life of 50 years

Expected service life of building: 50 years

Service life of product: 50 years

Thickness: 12.5 mm

Place of manufacture: Kalmarleden 50, 746 37 Bålsta, Sweden

The attached EPD models a service life of 50 years. In reality, the product and building service life may exceed the timescale modelled, in which case the impacts would be spread over an extended period, but 50 years was used here to conform to the requirements set out in the Saint-Gobain Methodological Guide and ensure transparency.

### Product specification:

Material	Part %	Quantity kg/FU
Gypsum	93.3	13.06
Paper liner	5.1	0.71
Additives	1.6	0.23
SUM	100	14.00

Declaration compiled by:  
Vikki Holme, Rosie Ryan and Ivan Mårtensson  
Contact person: Ivan Mårtensson  
Telephone: +46171415452  
Email: [ivan.martensson@gyproc.com](mailto:ivan.martensson@gyproc.com)

Environmental Indicators per FU:		
Climate Change – Global Warming	5.85	kg CO <sub>2</sub> equivalents
Water consumption	22.5	litres
Energy use	95.1	MJ
Recycled materials use	53.6	%

Verification of data:  
Independent verification of data and other environmental information has been carried out by Elin Eriksson at IVL Swedish Environmental Research Institute in accordance with ISO14025, §8.1.3

About The International EPD® System: EPDs within the same product category but from different programmes may not be comparable. For more information — [www.environdec.com](http://www.environdec.com)  
A critical review has been carried out by Michaël Medard (Saint-Gobain) in accordance with ISO 14044 clause 6.

# 1. Product characterisation

## 1.1. Definition of the functional unit (FU)

1 m<sup>2</sup> of installed building board with a specified function and an expected average service life of 50 years (packaging included).

Note: Gyproc Golvgips – Floor Board is installed with the use of screws, jointing compound and jointing tape; these are therefore included in the assessment.

## 1.2. Data type and quantity for the calculation of the functional unit (FU)

Quantity of product contained in the functional unit on the basis of a reference service life	
Average thickness:	12.5 mm
Total weight:	14.00 kg/m <sup>2</sup>
Amount of gypsum used:	13.06 kg/m <sup>2</sup> (93.3 %)
Paper lining used:	0.71 kg/m <sup>2</sup> (5.1 %) Surface with enhanced hardness
Various additives used:	0.23 kg/m <sup>2</sup> (1.6 %)
Distribution packaging	
Polyethylene:	0.002 kg/m <sup>2</sup>
Recycled Gypsum Dunnage:	0.29 kg/m <sup>2</sup>
Additional product	
Complementary products (type and quantity) to 1 m <sup>2</sup> for installation are:	
Screws:	8 pc/m <sup>2</sup> (each 1.25 g/pc) Steel screws
Jointing Compound:	0.33 kg/m <sup>2</sup> Commonly plaster compound
Jointing Tape:	1.23 m/m <sup>2</sup> Commonly paper based tape

### Justification of quantities supplied

The rate of scrap during the installation of the board and additional products is estimated to be: 1.3 % per FU.

Maintenance (including partial replacement if necessary): No maintenance or replacement is expected during the life time and this is therefore not modelled.

### Allocation rules

Gyproc AB produces Gyproc Golvgips along with other products. In order to calculate the LCA, a proportion of the consumption of production inputs (energy, raw materials etc.) and the production of outputs (emissions, waste etc.) have been allocated to Gyproc Golvgips.

The allocation has been made relative to the mass of the product.

### Consumption of chemicals on the Swedish observation list

None

### 1.3. Technical characteristics and useful information not included in the functional unit

Gyproc Golvgips – Floor Board contains 93.3 % Gypsum in a blend of Flue Gas Desulphurised Gypsum (DSG), recycled gypsum and natural gypsum. Recycled gypsum (DSG, Reprocessed internal gypsum production residue, Recycled Construction and Demolition Waste Gypsum) makes up 52 % of the gypsum blend.

The life cycle inventory data set out below has been calculated for the functional unit defined in The International EPD® System PCR 01.

### 1.4. System boundary

Building life cycle information														
A 1 - 3			A 4 - 5		B 1 - 7					C 1 - 4				
Product stage			Construction Process stage		Use stage					End of Life stage				
A1	A2	A3	A4	A5	B1	B2	B3	B4	B5	C1	C2	C3	C4	
Raw material supply	Transport	Manufacturing	Transport	Construction installation process	Use	Maintenance (Incl. transport)	Repair (Incl. transport)	Replacement (Incl. transport)	Refurbishment (Incl. transport)	Deconstruction	Transport	Waste processing	Disposal	
			Scenario	Scenario	Scenario	Scenario	Scenario	Scenario	Scenario	Scenario	Scenario	Scenario	Scenario	
			B6		Operational energy use									
			Scenario											
			B7		Operational water use									
			Scenario											

Included

Excluded

## 2. Contribution of the product to environmental impacts in accordance with EPD® PCR 01 §11.2.4

All these impacts are reported or calculated in accordance with §11.2.4 of The International EPD® System PCR 01 and §9.4 of the Saint-Gobain Methodological Guide and the data below are derived from the process of life cycle analysis.

The units of reference are defined by The International EPD® System PCR 01 §5 and the totals per functional unit (FU) are related to the Typical Life Time (TLT) of the product i.e. 50 years.

№	Flow	Environmental Impact per FU							
		Unit	Production stage	Construction stage		Use stage	End of Life stage	Reference service life	
				Transport	Installation				
1	Total primary energy	MJ	91.45	0.43	3.06	0.0	0.1602	95.1	
	Renewable energy	MJ	4.42	0.0005	0.4653	0.0	0.0002	4.89	
	Non-renewable energy	MJ	87.03	0.43	2.57	0.0	0.1599	90.2	
2	Abiotic resource depletion (ADP) in (Sb) antimony equivalents	kg	0.0363	0.0002	0.0010	0.0	0.0001	0.0375	
	Renewable material	kg	Paper liner: This material is made of recycled paper fibres					0.71	
	Non-renewable material	kg	Natural gypsum: This is an infinitely recyclable mineral					6.27	
3	Water consumption	litre	20.57	0.0326	1.9168	0.0	0.0152	22.5	
4	Recovered waste (total)	kg	1.4410	1.180E-07	0.1005	0.0	7.28	8.82	
	Disposed of waste	Hazardous waste	kg	0.0686	8.139E-06	0.0004	0.0	3.845E-06	0.0691
		Non-hazardous waste	kg	0.0762	8.373E-06	0.0986	0.0	6.72	6.9
		Inert waste	kg	1.7507	1.415E-05	0.0403	0.0	6.692E-06	1.791
		Radioactive waste	kg	1.001E-03	5.423E-06	4.536E-06	0.0	2.561E-06	0.001013
5	Climate change in CO <sub>2</sub> equivalents	kg	5.64	0.03	0.16	0.0	0.01	5.85	
6	Acidification potential in SO <sub>2</sub> equivalents	kg	0.0662	0.0003	0.0006	0.0	0.0001	0.0672	
7	Ozone depletion potential (ODP)	No emission of CFCs or HFCs						N/A	
8	Photochemical ozone creation potentials (POCP) in ethene equivalents	kg	0.0054	0.0000	3.553E-05	0.0	1.667E-05	0.00545	
9	Eutrophication potential in PO <sub>4</sub> <sup>3-</sup> equivalents	kg	0.0013	4.0269E-07	0.0000	0.0	0.0004	0.0018	

Electricity model: Production of electricity in Sweden (2004), predefined in TEAM (CO<sub>2</sub> factor: 1.03954 g/MJ). See reading guide, page 5

## For more information

The information provided for the purpose of producing this EPD was supplied by Gyproc AB.

### Traceability

The manufacturer which has participated in this study is: Gyproc AB

Contact: Ivan Martensson

Tel: +46171415452

Email: [ivan.martensson@gyproc.com](mailto:ivan.martensson@gyproc.com)

Contact for the primary data (headquarters): [epd.gypsum@saint-gobain.com](mailto:epd.gypsum@saint-gobain.com)

Life Cycle Inventories were made in 2012 and aggregation/calculation of data is done by TEAM™ software version 4.0.

### Reading Guide

Reading example:  $-9.0E-03 = -9.0 \times 10^{-3}$